

## Data Sheet: SNU



- > SNU 5 AU
- > SNU 10 AU







## **OPEN VENTED COMPACT STORAGE WATER HEATER**

Made in Germany the STIEBEL ELTRON SNU 5 and SNU 10 under sink open vented water heaters deliver hot water quickly to a single sink. These point of use water heaters eliminate long runs of pipework for isolated sinks and reduce the waiting time for hot water to arrive at the outlet.

		PLUS		
Model		SNU 5	SNU 10	
		229467	229468	
Tank capacity	L	5	10	
Rated output (240 V)	kW	2.2	2.2	
Rated current (240 V)	Α	9.1	9.1	
Connection		1/N/PE	1/N/PE	
Fuse protection	A	10	10	
Electrical installation		As per AS/NZS3000		
Installation requirements		AS/NZS3500.4.2 & local requirements		
Temperature settings	°C	30-85	30-85	
Mixed water volume at 40 °C	L	10	19	
Water connection		G 3/8 A	G 3/8 A	
Max. appliance permissible				
pressure	kPa	0	0	
Max. tapware permissible pressure	kPa	500	500	
Standby energy consumption / 24				
h at 65 °C	kWh	0.20	0.32	
IP rating		IP24 D	IP24 D	
Height	mm	421	503	
Width	mm	263	295	
Depth	mm	230	275	
Weight	kg	3.0	4.6	
Colour		White	White	
Approvals		WaterMark Lic No. \	WaterMark Lic No. WMKA00301. AS3498	


The SNU under sink point of use water heater is open vented and must be installed with a STIEBEL ELTRON open vented tap. Not suitable for installation at a basin as a tempering valve or TMV cannot be fitted with this water heater.







SNU



**SNU Dimensions** 

STIEBEL ELTRON is committed to our policy of continual improvement, some features may have subsequently been changed or even removed.

Our advisors will be happy to consult with you regarding the currently applicable equipment features. The images used in this data sheet are for reference only.