

**STIEBEL ELTRON**

# WPE-I H 400

## Premium

Combine comfort and  
functionality into one  
home solution



WPE-I H 400

GEOTHERMAL HEAT PUMPS

Hot water, heating and cooling on a grand scale

The WPE-I heat pump provides not only heating and cooling but also hot water convenience. The cascade control can supply both apartment buildings and commercial properties. With its inverter technology, the appliance is exceptionally versatile, and can even be conveniently operated via an app (optional accessory required).

Product features

- › Geothermal hydronic heat pump for domestic or commercial applications
- › Inverter technology
- › Simultaneous heating and cooling
- › Cascadable with 16 devices from 10 kW to 1.6 MW
- › Quiet operation



GEOTHERMAL & INVERTER

UP TO 1.6 MW



Type	PREMIUM			
	WPE-I 33 H 400	WPE-I 44 H 400	WPE-I 59 H 400	WPE-I 87 H 400
Article no.	201412	201413	201414	201415
Output at B0/W35 (EN 14511)	20.18	26.71	35.60	52.00
Heating output at B0/W35 (min/max)	10 – 33	11 – 44	14 – 59	21 – 87
SCOP (EN 14825)	5.55	5.56	5.19	5.17
Coefficient of performance at B0/W35 (EN 14511)	4.73	4.60	4.50	4.71
Flow rate, heat source side	7.63	9.75	12.38	18.79
Max. heating flow temperature	65	65	65	65
Sound power level (EN 12102)	41-56	41-56	46-61	46-61
Connection	3/N/PE	3/N/PE	3/N/PE	3/N/PE
Rated voltage	400	400	400	400
Max. operating current	25.2	29.3	39.8	54.2
Electrical installation	As per AS/NZS3000			
Refrigerant	R410A	R410A	R410A	R410A
Height	1723	1723	1742	1742
Width	692	692	900	900
Depth	803	803	848	848
Weight	300	300	430	430



STIEBEL ELTRON is committed to our policy of continual improvement, some features may have subsequently been changed or even removed. Our advisors will be happy to consult with you regarding the currently applicable equipment features. The images used in this data sheet are for reference only.